




BestLight LED

Redefining the LED Marketplace


8909 East Ave
Mentor, OH 44060

440-205-1552
<http://bestlightled.com>

LED Corn Light



E-26
Medium or
Edison



E-39
or
Mogul



Part No.	CLI-5W-E26-XK	CLI-7W-E26-XK	CLI-9W-E26-XK	CLI-12W-E26-XK	CLI-15W-E26-XK
Wattage	5W	7W	9W	12W	15W
CCT	2700-6500K	2700-6500K	2700-6500K	2700-6500K	2700-6500K
Lumens	470-550	660-770	850-990	1,140-1,320	1,500-1,720
CRI	>80	>80	>80	>80	>80
IP Rating	IP64	IP64	IP64	IP64	IP64
Input Voltage	AC100-277V	AC100-277V	AC100-277V	AC100-277	AC100-277
Beam Angle	360°	360°	360°	360°	360°
Equivalent	11W CFL / 2W MHL, HPS, HID	14W CFL / 20W MHL, HPS, HID	18W CFL / 35W MHL, HPS, HID	23W CFL / 35W MHL, HPS, HID	30W CFL / 50W MHL, HPS, HID
Base and Size	E26 - 5.1" x 1.8"Ø	E26 - 5.1" x 1.8"Ø	E26 - 5.7" x 1.8"Ø	E26 - 6.5" x 1.8"Ø	E26 - 6.5" x 2.2"Ø

Part No.	CLI-20W-XX-XK	CLI-30W-XX-XK	CLI-40W-XX-XK	CLI-60W-E39-XK
Wattage	20W	30W	40W	60W
CCT	2700-6500K	2700 - 5700K	4000K-5700K	4000-5700K
Lumens	2000-2300	3,100 - 3,600	2,400-2,800	6,000-7,000
CRI	>80	>80	>80	>80
IP Rating	IP64	IP40	IP64	IP64
Input Voltage	AC100-277V	AC100-277	AC100-277	AC100-277V
Beam Angle	360°	360°	360°	360°
Equivalent	CFL:26W/8T4/Q/G24d/PH	200W incandescent / 60W CFL	80W CFL / 150W MHL, HPS, HID	120W CFL / 175W MHL, HPS, HID
Base and Size	E26 - 7.3" x 2.2"Ø	E26 - 8.9" x 3.7"Ø E39 - 9.1" x 3.7"Ø	E26 - 9.9" x 3.7"Ø E39 - 10.2" x 3.7"Ø	E26 - 10.9" x 3.7"Ø E39 - 11.2" x 3.7"Ø

Part No.	CLI-80W-E39-XK	CLI-100W-E39-XK	CLI-120W-E39-XK	CLI-150W-E39
Wattage	80W	100W	120W	150W
CCT	4000-5700K	4000-5700K	4000-5700K	4000-5700K
Lumens	8,000-8,900	10,000-11,500	12,000-13,500	15,000-16,500
CRI	>80	>80	>80	>80
IP Rating	IP64	IP64	IP64	IP64
Input Voltage	AC100-277V	AC100-277V	AC100-277V	AC100-277V
Beam Angle	360°	360°	360°	360°
Equivalent	120W CFL / 175W MHL, HPS, HID	200W CFL / 250W MHL, HPS, HID	200W CFL / 400W MHL, HPS, HID	400W MHL, HPS, HID
Base and Size	E39 - 10.6" x 5"Ø	E39 - 11.4" x 5"Ø	E39 - 12.2" x 5"Ø	E39 - 13.2" x 5"Ø

